

C2C

Make it easy to keep an eye on what's happening in any room.



Specifications

Model Parameters

Name	C2C (Mini O Plus)	C2C (Mini O)
Model	CS-CV206-C0-3B2WFR	CS-CV206-C0-1A1WFR

Camera

Image Sensor	1/2.7"2MP HD progressive scan CMOS	1/4" 1MP HD progressive scan CMOS
Shutter Speed	Self-adaptive shutter	Self-adaptive shutter
Lens	2.8mm@F2.0, Horizontal angle: 115°, Diagonal angle: 135°	2.8mm@F2.5, Horizontal angle: 90°, Diagonal angle: 111°
Lens Mount	M12	M12
Day & Night	IR-cut filter with auto-switching	IR-cut filter with auto-switching
DNR	3D DNR	3D DNR
WDR	Digital WDR	Digital WDR

Compression

Video Compression	H.264	H.264
H.264 Type	Main profile	Main profile
Video Bit Rate	HD, balanced and smooth bit rate	HD, balanced and smooth bit rate

Image

Max. Resolution	1920×1080	1280×720
Image setting	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support	Support

Network

Storage	Support Micro SD card (Max. 256G)	Support Micro SD card (Max. 256G)
Smart Alarm	Motion detection	Motion detection
Wi-Fi Pairing	SmartConfig (Wi-Fi One-Key Configuration)/AP pairing	SmartConfig (Wi-Fi One-Key Configuration)/AP pairing
Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark
Minimum Network Requirements	2M	1M

Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 150 Mbps	11b: 11 Mbps, 11g: 54 Mbps, 11n: 150 Mbps

General

Operating Conditions	-10°C ~ 50°C (14°F ~ 122°F), Humidity 95% or less (non-condensing)	-10°C ~ 50°C (14°F ~ 122°F), Humidity 95% or less (non-condensing)
Power Supply	DC 5V±10%	DC 5V±10%
Power Consumption	Max. 3W	Max. 3W
IR Range	Max. 7.5 meters	Max. 7.5 meters
Product Dimensions	128mm x 58mm x 38mm	128mm x 58mm x 38mm
Packaging Dimensions	149mm x 87.5mm x 91.5mm	149mm x 87.5mm x 91.5mm
Weight	120g	120g