SOMtouch

2-command radio wall button



Advantages:

- Bi-directional SOMloq2 radio system
- Downward compatible with the Somloq Rollingcode radio system, making it possible to control existing operators and radio receivers
- Battery operation no additional installation effort is necessary

Advantages of SOMloq2:

- Option of querying door position/ receiver status using the small button without travel motion
- Maximum protection from hackers with 128 bit AES encryption with Rollingcode
- Feedback of radio commands by LED
- Improved range and higher reliability due to the hop function, since the signal is actively forwarded by SOMloq2 receivers

TECHNICAL DATA

Radio system	SOMloq2
Radio commands	2
Frequency	FM 868,8 MHz
	FM 868,95 MHz
Range ¹⁾	approx. 50 m
Dimensions	80×85×14 mm

🗊 Disturbance-resistant radio signal 🛱 128-bit AES encryption 🤶 Bi-directional radio control system

1) Depending on surroundings. Last updated: 05/2016. Literal errors, errors and technical changes excepted.



SOMMER ANTRIEBS- UND FUNKTECHNIK GMBH | HANS-BÖCKLER-STR. 21-27 | D-73230 KIRCHHEIM/TECK PHONE +49 7021 8001-0 FAX +49 7021 8001-100 INFO@SOMMER.EU WWW.SOMMER.EU

SOMMERGMBH SOMMER_GMBH